Swing Range





Design and user interface

- Elegant and uncluttered design.
- Capacitive keyboard and wide graphical display.
- LED lighting of the white cell for a maximum visibility of the displayed products.



Maximum flexibility

- Swing is available as a Slave model to
- Up to 7 trays which can be easily moved thanks to Vertical Flex (V-Flex)
- Space optimization inside the cell.
- With two optional Visioshop trays it is possible to create a special area for products with non standard packaging, such as salads and ready to go meals.
- Enhanced ETL trays.
- Wider delivery bin.



High energy efficiency

- C class according to EN 50597 scale.
- Perfect insulation of the cabinet.
- Cooling unit with R290 gas.

Electronics

solutions.

• Swing is compatible with Newis

completely touchless mode.

the machine remotely.

 With Breasy it is possible to select and pay for your product in a

With AmiClo it is possibile to set up

- High energy efficieny and dramatic decrease of pull down time.
- Swing can manage up to three temperatures inside the cell or can be set with a 100% Food or Ambient layouts.



An elegant and

uncluttered design

High visibility cell

Swing is available as a Slave model to

Swing Range










Height	1830 mm
Width	900 mm
Depth	790 mm
Weight	300 kg ca.

Energy consumption labels







necta.evocagroup.com



. . .

Via Roma 24, 24030 Valbrembo (BG) Italia Tel. +39 035 606111 - Fax +39 035 606519









