



There's no longer any need to make room for a boiler and a chiller. The FilterFlow Combined Water Boiler and Chiller does both jobs perfectly. It's compact, but extremely versatile and flexible. Whether you're in the mood for a warming hot drink or a refreshingly cool glass of water, the boiler / chiller won't let you down. Its intuitive, touch screen display means it's easy to use too.

#### PRODUCT OPTIONS AND ACCESSORIES

- DP10 DESCALER POWDER
- FC04 EBFX WATER FILTER - FROM 2015
- PI36 INLET CONNECTION HOSE EB

#### PRODUCT FEATURES

- Convenient push button operation, ideal for front of house and self service
- Filtered chilled and hot water on tap 24 hours a day, space saving and economic - no need for a separate boiler and chiller
- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge
- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit



# LINCAT FILTERFLOW COUNTER-TOP COMBINED WATER BOILER & CHILLER WITH PUSH BUTTON DISPENSE - W 250 MM - 3.0 KW

## MODEL: EB3FX/HC/PB

### WEIGHTS & DIMENSIONS

Width	250 mil
Depth	570 mil
Height	595 mil
Weight	24.8 kg

### SHIPPING DETAILS

Ship Width	65 cm
Ship Depth	38 cm
Ship Height	88 cm
Ship Weight	27.28 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	13	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	3000	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	3 kW	Energy Saving	Yes

### ADDITIONAL SPECIFICATIONS

Capacity Volume	7 l	Hourly Number of Hot Cups	140
Control Type	Electronic	Internal Filter	Yes
Dispense Actuation Method	Push-Button	Rapid Draw Off Hot	5 l
Drip Pan	Yes	Rapid Draw Off Hot Cups	25 C
Hourly Cold Water Output	12 l	Temperature Maximum	98 °C
Hourly Hot Water Output	28 l	Temperature Minimum	11 °C
Hourly Number of Cold Cups	60		

### BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
January 23, 2024

TECHNICAL DRAWING

